

CA8SD Mini Wedge

SINGLE DRIVER



Monitors designed by musicians and engineers that make sense, look great, and sound fabulous!

The Centerline Acoustics CA8SD 8" Single Driver Mini Wedge is a full range driver floor wedge designed to meet the need for a high-quality, high-output floor monitor wedge where tight space, low weight, and high clarity is a consideration. So, what do we mean by "Single Driver"? Simply put, this is not a coaxial driver monitor but is just a single driver. No woofer, no high frequency compression driver, and no two way crossover, just one driver covering from around 100hz up to 16khz with a sweet and easy roll-off of the highs at around 10khz. The only other device in the box other than the driver is a high-pass filter that acts as a protecting device when extreme low frequencies are present.

Other innovations that make sense are features such as Speakon jacks on both sides of the enclosure; not two on one side or two on the back. Your cables will never be in the way regardless if you are daisy-chaining, or which side your floor box happens to be located. Plus, the #2 hot and cold connector pins of the Speakon jacks are wired to pass-through which means you can run two individual mixes down one 4-conductor cable.

The CA8SD enclosure is made of Baltic birch plywood cut on a CNC machine, glued and stapled, then sprayed in a textured Polyurea coating for Sherman Tank-like construction.

Each unit is hand made right here in Nashville, TN-Music City USA, so you can feel good knowing you are supporting a local American business that lives and breathes superb audio. Yes, it is cute, but it packs a serious punch with tone for days. The pic just doesn't do it justice, because it looks fabulous in person! A great sounding floor wedge that the everyone can afford, use,

The ultimate hot-spot monitor. Great for church stages, choir spots, theatre stages, & orchestra pits. Smooth sound, high output, and studio monitor fidelity.



Specifications

Coverage Pattern.....	80° conical
Operating Frequency Range	100 Hz –16kHz
Sensitivity @ 1M	90dB SPL
Maximum Output ..	105dB SPL Cont., 114dB SPL Program
Input Power Ratings	200 W continuous, 350 W program
Nominal Impedance	8 ohms
Recommended Filter.....	170 Hz HP @ 24 dB/ Butterworth
Drivers	1 x 8" Full Range
Connectors.....	2-NL4
Enclosure Material.....	13ply Baltic Birch Plywood
Finish.....	Black Polyurea Coating
Possible Angles.....	30, 60, and 90 Degrees.
Dimensions.....	10 x 10 x 10 Inches
Weight.....	7lbs
Warranty.....	5 Years
Unilateral Fixed Price.....	\$499.00 USD

FREQUENCY RESPONSE

